

Stoßverbinder

- Kupfer, verzinkt • Isolierhülle: Polyolefin mit Innenkleber
- RoHS-konform

Art. Nr.	LQ	A	GL	kg/100	VE
363500	0,5-1,0	14	36	0,120	500 100
363502	1,5-2,5	15	36	0,132	500 100
363504	4,0-6,0	15	41	0,300	500 100



Flachsteckhülsen

- Messing, verzinkt • Isolierhülle: Polyolefin mit Innenkleber
- RoHS-konform

Art. Nr.	LQ	FSt.	GL	B	B	kg/100	VE
363510	0,5-1,0	6,3x0,8	30,0	6,6	6,6	0,129	500 100
363512	1,5-2,5	6,3x0,8	30,0	6,6	6,6	0,138	500 100
363514	4,0-6,0	6,3x0,8	30,0	6,6	6,6	0,200	500 100



Flachstecker

- Messing, verzinkt • Isolierhülle: Polyolefin mit Innenkleber
- RoHS-konform

Art. Nr.	LQ	FSt.	GL	B	B	kg/100	VE
363520	0,5-1,0	6,3x0,8	30,0	6,6	6,6	0,092	500 100
363522	1,5-2,5	6,3x0,8	30,0	6,6	6,6	0,106	500 100
363524	4,0-6,0	6,3x0,8	30,0	6,6	6,6	0,159	500 100



Ringkabelschuhe

- Kupfer, verzinkt • Isolierhülle: Polyolefin mit Innenkleber
- RoHS-konform

Art. Nr.	LQ	M	d2	GL	B	B	kg/100	VE
363530	0,5-1,0	4	4,3	28,5	8,0	8,0	0,073	500 100
363532		5	5,3	28,5	8,0	8,0	0,066	500 100
363534		6	6,5	34,5	11,6	11,6	0,104	500 100
363536		8	8,4	34,5	11,6	11,6	0,089	500 100
363538		10	10,5	37,5	13,6	13,6	0,112	500 100
363540	1,5-2,5	4	4,3	30,5	8,5	8,5	0,085	500 100
363542		5	5,3	30,5	9,5	9,5	0,083	500 100
363544		6	6,5	35,5	12,0	12,0	0,122	500 100
363546		8	8,4	35,5	12,0	12,0	0,118	500 100
363548		10	10,5	37,5	13,6	13,6	0,128	500 100
363550	4,0-6,0	4	4,3	34,2	9,5	9,5	0,173	500 100
363552		5	5,3	34,0	9,5	9,5	0,172	500 100
363554		6	6,5	37,5	12,0	12,0	0,201	500 100
363556		8	8,4	42,0	15,0	15,0	0,251	500 100
363558		10	10,5	42,0	15,0	15,0	0,226	500 100



Löt-Schrumpfverbinder

- Kupfer, verzinkt • RoHS-konform • kein Presswerkzeug nötig
- Isolierhülle: Polyolefin mit Innenkleber

Art. Nr.	LQ	kg/100	VE
363600	0,5-1,0	0,090	1
363602	1,5-2,5	0,110	1
363604	4,0-6,0	0,160	1

