
















Gabelkabelschuhe DIN 46237

- aus Elektrolyt-Kupfer, verzinkt • PVC-isoliert, mit aufgeweiteter Isolierhülse
- geeignet für harmonisierte Leitungen • Easy Entry

PVC
75°



Art. Nr.	LQ	M	d2	d1	d4	s1	A	GL	E	B	kg/100		VE	
260300	0,5-1,0	3	3,2	1,95	4,2	0,8	10,4	20,0	6,7	5,6	0,065	500	100	
260302		3,5	3,7	1,95	4,2	0,8	10,4	19,4	6,5	6,5	0,065	500	100	
260304		4	4,2	1,95	4,2	0,8	10,4	20,9	6,3	6,4	0,070	500	100	
260306		5	5,2	1,95	4,2	0,8	10,4	21,2	8,0	8,0	0,092	500	100	
260308		6	6,2	1,95	4,2	0,8	10,4	22,4	8,3	9,2	0,101	500	100	
260310	1,5-2,5	3	3,2	2,45	4,8	0,8	11,0	23,0	8,4	5,6	0,079	500	100	
260312		3,5	3,7	2,45	4,8	0,8	11,0	20,3	5,3	6,6	0,085	500	100	
260314		4	4,2	2,45	4,8	0,8	11,0	20,3	5,3	6,6	0,084	500	100	
260316		5	5,2	2,45	4,8	0,8	11,0	25,0	9,5	9,1	0,109	500	100	
260318		6	6,3	2,45	4,8	0,8	11,0	27,0	11,2	10,0	0,118	500	100	
260320	4,0-6,0	4	4,2	3,5	6,6	1,0	14,0	26,0	7,2	8,1	0,116	500	100	
260322		5	5,2	3,5	6,6	1,0	14,0	28,5	10,5	9,0	0,179	500	100	
260324		6	6,3	3,5	6,6	1,0	14,0	29,5	11,0	11,0	0,188	500	100	
260326		8	8,2	3,5	6,6	1,0	14,0	35,2	15,0	15,2	0,229	500	100	
260328		10	10,5	3,5	6,6	1,0	14,0	38,0	16,6	19,0	0,291	500	100	